

## PARAPROJECT® CASE i16 KidsCover

## CHARGE, SYNC, TRANSPORT & PROTECT





dimensions in mm

part number EU version: 208.640-17001 GTIN / EAN 4006793002210 field of application education, health care certificates CE / RAHS / REACH applicable standards DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024  To Law Version of Connector with LED display on 1x USB connection cable EU, length: 5 m 1x USB connection cable EU, lengt		
GTIN / EAN         4006793002210           field of application         education, health care           certificates         CE / RoHS / REACH           applicable standards         DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024           applicable standards         J16x USB data and charging cable to lightning connector with LED display - 1x device connection cable EU, length: 5 m - 1x USB connection cable, length: 3 m - 1x USB connection cable, length: 3 m - 1x y-adaptor with 1x Euro flat plug (2-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x user guide for combination lock - 1x user manual - 1x user guide for combination lock - 1x user manual - 0 - outer shell made from UV-proof ABS-PMMA plastic with a wall thickness of 3 mm, white - circumferential aluminum frame on lid and body - pockets made from _Con-Pearl** material - bottom tray of the case is fully lined with foam material  - 4x smooth-running ball bearings (with 2 lockable castors) - telescopic handle, 4-fold - carrying handles on both sides  external dimensions  width 720 x depth 390 x height 550 mm  empty weight  15.2 kg shipping weight  17.75 kg  transport dimensions  width 760 x depth 420 x height 570 mm  number of euro-paletts  dimensions of euro-paletts  width 1,200 x depth 800 x height 1,860 mm  euro-paletts  dimensions  42021250	description	PARAPROJECT® CASE i16 KidsCover for iPad; white
field of application         education, health care           certificates         CE / ROHS / REACH           applicable standards         DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024           applicable standards         -16x USB data and charging cable to lightning connector with LED display - 1x device connection cable EU, length: 5 m - 1x USB connection cable, length: 3 m - 1x USB connection cable, length: 3 m - 1x y-adaptor with 1x Euro flat plug (2-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x y-adaptor with 1x Euro flat plug (2-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x user manual           materials         - outer shell made from UV-proof ABS-PMMA plastic with a wall thickness of 3 mm, white - circumferential aluminum frame on lid and body - pockets made from "Con-Pearle" material - bottom tray of the case is fully lined with foam material           transport         - 4x smooth-running ball bearings (with 2 lockable castors) - telescopic handle, 4-fold - carrying handles on both sides           external dimensions         width 720 x depth 390 x height 550 mm           empty weight         15.2 kg           shipping weight         17.75 kg           transport dimensions         width 760 x depth 420 x height 570 mm           number of euro-paletts         did with 1,200 x depth 800 x height 1,860 mm           customs tariff no.         42021250	part number	EU version: 208.640-17001
certificates       CE / RoHS / REACH         applicable standards       DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024         applicable standards       16x USB data and charging cable to lightning connector with LED display - 1x device connection cable EU, length: 5 m - 1x USB connection cable EU, length: 3 m - 1x y-adaptor with 1x IBM socket (C5, 3-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x y-adaptor with 1x Euro flat plug (2-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x user guide for combination lock - 1x user manual         materials       - outer shell made from UV-proof ABS-PMMA plastic with a wall thickness of 3 mm, white - circumferential aluminum frame on lid and body - pockets made from "Con-Pearle" material - bottom tray of the case is fully lined with foam material - bottom tray of the case is fully lined with foam material - bottom tray of the case is fully lined with foam material - telescopic handle, 4-fold - carrying handles on both sides         external dimensions       width 720 x depth 390 x height 550 mm         empty weight       15.2 kg         shipping weight       17.75 kg         transport dimensions       width 760 x depth 420 x height 570 mm         number of euro-paletts       6         dimensions of euro-paletts       width 1,200 x depth 800 x height 1,860 mm         customs tariff no.       42021250	GTIN / EAN	4006793002210
applicable standards  DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024  - 16x USB data and charging cable to lightning connector with LED display - 1x device connection cable EU, length: 5 m - 1x USB connection cable, length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption and length: 3 m - 1x USB connection cable etc., seption called etc., sep	field of application	education, health care
- 16x USB data and charging cable to lightning connector with LED display - 1x device connection cable EU, length: 5 m - 1x USB connection cable, length: 3 m - 1x y-adaptor with 1x IBM socket (C5, 3-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x y-adaptor with 1x Euro flat plug (2-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x user guide for combination lock - 1x user manual  - outer shell made from UV-proof ABS-PMMA plastic with a wall thickness of 3 mm, white - circumferential aluminum frame on lid and body - pockets made from "Con-Pearl®" material - bottom tray of the case is fully lined with foam material - bottom tray of the case is fully lined with foam material - 4x smooth-running ball bearings (with 2 lockable castors) - telescopic handle, 4-fold - carrying handles on both sides  external dimensions width 720 x depth 390 x height 550 mm  empty weight  15.2 kg shipping weight  17.75 kg  transport dimensions width 760 x depth 420 x height 570 mm  number of euro-paletts  6 dimensions of euro-palett  width 1,200 x depth 800 x height 1,860 mm  customs tariff no. 42021250	certificates	CE / RoHS / REACH
connector with LED display - 1x device connection cable EU, length: 5 m - 1x USB connection cable, length: 3 m - 1x y-adaptor with 1x IBM socket (C5, 3-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x y-adaptor with 1x Euro flat plug (2-pin) and 1x Euro-8 socket (C7, 2-pin) - 1x user guide for combination lock - 1x user manual  - outer shell made from UV-proof ABS-PMMA plastic with a wall thickness of 3 mm, white - circumferential aluminum frame on lid and body - pockets made from "Con-Pearl®" material - bottom tray of the case is fully lined with foam material  - 4x smooth-running ball bearings (with 2 lockable castors) - telescopic handle, 4-fold - carrying handles on both sides  external dimensions  width 720 x depth 390 x height 550 mm  empty weight  15.2 kg shipping weight  17.75 kg  transport dimensions  width 760 x depth 420 x height 570 mm  number of euro-paletts  dimensions of euro-paletts  width 1,200 x depth 800 x height 1,860 mm  customs tariff no.  42021250	applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024
ransport carrying handles on both sides external dimensions width 720 x depth 390 x height 570 mm  ransport dimensions width 760 x depth 420 x height 570 mm  number of euro-palletts  dimensions of euro-pallet customs tariff no.  - circumferential aluminum frame on lid and body - pockets made from "Con-Pearl®" material aluminum frame on lid and body - pockets made from "Con-Pearl®" material aluminum frame on lid and body - pockets made from "Con-Pearl®" material aluminum frame on lid and body - pockets made from "Con-Pearl®" material aluminum frame on lid and body - pockets made from "Con-Pearl®" material - bottom frame on lid and body - pockets made from "Con-Pearl®" material - bottom frame fold with 2 lockable castors)  - 4x smooth-running ball bearings (with 2 lockable castors) - telescopic handle, 4-fold - carrying handles on both sides  external dimensions  width 720 x depth 390 x height 550 mm  frame on lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid aluminum frame in lid and body - pockets fill aluminum frame in lid and body - pockets fill aluminum frame in lid aluminum frame in lid and body - pockets fill aluminum frame in lid alum	scope of delivery	connector with LED display  - 1x device connection cable EU, length: 5 m  - 1x USB connection cable, length: 3 m  - 1x y-adaptor with 1x IBM socket (C5, 3-pin) and 1x Euro-8 socket (C7, 2-pin)  - 1x y-adaptor with 1x Euro flat plug (2-pin) and 1x Euro-8 socket (C7, 2-pin)  - 1x user guide for combination lock
transport - telescopic handle, 4-fold - carrying handles on both sides  external dimensions width 720 x depth 390 x height 550 mm  empty weight 15.2 kg  shipping weight 17.75 kg  transport dimensions width 760 x depth 420 x height 570 mm  number of euro-paletts  dimensions of euro-pallet width 1,200 x depth 800 x height 1,860 mm  customs tariff no. 42021250	materials	- circumferential aluminum frame on lid and body - pockets made from "Con-Pearl®" material
empty weight 15.2 kg shipping weight 17.75 kg transport dimensions width 760 x depth 420 x height 570 mm number of euro-paletts dimensions of euro-pallet width 1,200 x depth 800 x height 1,860 mm customs tariff no. 42021250	transport	- telescopic handle, 4-fold
shipping weight 17.75 kg transport dimensions width 760 x depth 420 x height 570 mm  number of euro-paletts dimensions of euro-pallet width 1,200 x depth 800 x height 1,860 mm  customs tariff no. 42021250	external dimensions	width 720 x depth 390 x height 550 mm
transport dimensions width 760 x depth 420 x height 570 mm  number of euro-paletts  dimensions of euro-pallet  customs tariff no. 42021250	empty weight	15.2 kg
number of euro-paletts 6 dimensions of euro-pallet width 1,200 x depth 800 x height 1,860 mm customs tariff no. 42021250	shipping weight	17.75 kg
euro-paletts  dimensions of euro-pallet  customs tariff no.  width 1,200 x depth 800 x height 1,860 mm  42021250	transport dimensions	width 760 x depth 420 x height 570 mm
euro-pallet width 1,200 x depth 800 x height 1,860 mm  customs tariff no. 42021250		6
		width 1,200 x depth 800 x height 1,860 mm
	customs tariff no.	42021250
country of origin EU	country of origin	EU



## PARAPROJECT® CASE i16 KidsCover

## CHARGE, SYNC, TRANSPORT & PROTECT

equipment	<ul> <li>case lid: with diverse pockets and compartments</li> <li>body: sync and charging unit, 2x storage space for 8 iPad each with KidsCover, storage compartment for master laptop</li> <li>additionally: air vents in the lid and bottom tray ensure optimum air circulation</li> <li>built-in programmable charging timer</li> <li>temperature sensor (overheating protection)</li> </ul>
compatible devices	all iPad 4G and beyond as well as all iPad Mini
max. number of devices	16
operating system	iOS
cable types for equipment	USB data and charging cable to lightning connector with LED display
power supply	central power unit for the entire power supply of devices
output power per port	2.4 A
optional accessories	KidsCover
locking system	combination lock
connections	outside: - central power supply with protective cap - USB-B terminal for sync - network connector (RJ45) for access point - optional HDMI port  inside: - 16x USB-A terminal for Flex2Connect - y-adaptor, C14 plug to 1 x IBM port (C5, 3-pin) and 1 x Euro-8 socket (C7, 2-pin, AUX 1) - y-adaptor, C14 plug to 1 x Euro flat plug and 1 x Euro-8 socket (C7, 2-pin, AUX 2)
data of currents	- 100 - 240 V - max. 3.6 A - 50/60 Hz
dimensions of iPad pockets	2 big storage compartments for 8 KidsCover each width 280 x depth 235 x height 320 mm
dimensions of notebook compartment	width 25 x depth 300 x height 320 mm





- sync and Charging unit (Switch On / Off)
- built-in programmable charging timer



- central power supply with protective cap
- USB-B terminal for sync
- network connector (RJ45) for access point
- optional HDMI port

dimensions in mm